

ULTRA PREMIUM EXTERIOR LOW SHEEN

RESOURCE CODE 51112-LINE

NOVEMBER 2013

PAGE 1 OF 3



EXTERIOR



WATER
WASH UP



TINTABLE

Description

Valspar Ultra Premium Paints are designed to make your painting project a more positive experience. Choose Valspar Exterior to be your all weather, all surface protector with the confidence of a Home-Life Warranty*

Valspar Exterior Low Sheen is a smooth acrylic paint designed to protect and decorate the outside of your home. This product provides a mould and algae-resistant film and protection against cracking, flaking and peeling. Valspar Exterior Paint provides complete protection.

* For full warranty details refer to: www.valspar.com.au or www.valspar.co.nz

Why Valspar?

- | | |
|--|---|
| <ul style="list-style-type: none"> • Home-Life Warranty* • All weather protection • UV protection | <ul style="list-style-type: none"> • Paint & Primer in One • Mould, dirt, tannin resistant • Resists colour fading |
|--|---|

Colours

White, Light, Mid and Strong bases; selected coloured bases and factory colours. Tint using Ecotint® to Valspar colours or other competitor colours.

Dries to a Low Sheen finish

Properties & Performance Guide

Dry & Recoat Times	Touch Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 14 M ² /L depending on the surface texture, porosity and method of application.
Thinning	Thinning is generally not required. If applying in hot or windy weather or onto very porous surfaces, thin the first coat only with up to 10% clean water. If necessary to aid spray atomisation, thin with up to 5% clean water.
Clean Up	Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 45g/Litre.

ULTRA PREMIUM

RESOURCE CODE 51112-LINE

NOVEMBER 2013

EXTERIOR LOW SHEEN

PAGE 2 OF 3

Before Painting

Read safety information below before painting.

- The surface must be clean, dry and free of dirt, chalk, loose friable material and grime.
- Glossy surfaces should be sanded to remove gloss before painting.
- Remove old, loose or flaking paint.
- Repair all damaged areas and sand smooth.
- If mould, moss, algae or lichen is present, it must be completely removed. Apply a solution of 1 part household bleach and 3 parts water. Rinse thoroughly with clean water. Allow to dry.
- Allow new LOSP treated pine to weather 2 weeks prior to application in order to ensure adhesion of the paint. Allow resin rich hardwoods to weather for 4-6 weeks. Knots in LOSP treated pine may be a source of resin bleed which will discolour white and white tones.
- If painting with white & white tone colours on a tannin rich timber, apply an initial coat of Valspar Exterior as a sealer.
- Some primers used on pre-primed timbers are of poor quality. Unless a painting specification is supplied by the timber manufacturer, pre-primed timber should be sanded back to bare before coating to ensure durability.
- Ensure all new cement and concrete surfaces are fully cured prior to painting. Typically this may take a minimum of 4-6 weeks. Ensure concrete surfaces are free from any bond breakers, formwork release agents, curing compounds and efflorescence (white salts).
- Ensure Zinalume® or weathered Colorbond® surfaces are clean and free of salts or other deposits. New Colorbond® should be cleaned with a nylon scourer if painting is required.
- Allow new galvanised iron sheet to weather until dull, then wash down. Alternatively thoroughly clean new sheets with a nylon scourer and detergent, then rinse.
- Galvanised steel (structural/hot dip): due to the possible variability in surfaces and exposure conditions, call the Valspar Hotline to determine the most suitable preparation prior to painting.
- Test soundness of previously painted surfaces. Unsound surfaces should be stripped for best results.
- Ferrous metal & wrought iron must be primed with a suitable metal primer. For longer lasting corrosion resistance, a complete metal protection system is recommended.
- *Not suitable for walk on or drive on areas or roofs where rainwater is collected.*

Application & After Painting

- Do not apply in damp or very humid conditions, or when rain is likely. Apply when the air and surface temperatures are above 10°C and below 35°C.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Check your colour is correct, as tinted paint is not refundable.
- When more than one container of the same colour is required, intermix containers to ensure colour uniformity. If you feel that you may run out of paint, stop at a corner or a natural break.
- Apply 2-3 full, even coats using a synthetic brush or, roller, or spray.
- Apply liberally, working from dry areas into the paint's wet edge and finish with gentle, vertical strokes. Avoid excessive rolling or brushing.

AFTER PAINTING

- Remove as much paint as possible from brushes and rollers before cleaning up in soapy water away from drains.
- Wipe up spills immediately with a damp cloth.

ULTRA PREMIUM

RESOURCE CODE 51112-LINE

NOVEMBER 2013

EXTERIOR LOW SHEEN

PAGE 3 OF 3

Usage Areas			
Usage	Suitable	Primer Recommended	Coats Required for Home- Life Warranty*
Timber and weatherboards	√	X	3
Brick, masonry and cement render	√	X	3
Fibre cement board	√	X	3
Previously painted surfaces	√	X	2
Zincalume	√	X	2 **
Galvanised iron sheet	√	X	2 **
Concrete	√	X	3
Ferrous metal & wrought iron	√	√	3

** 3 coats required within 1km of the coast

Additional Data
<p>Available in 1, 2, 4, 10 and 15 litre containers. Tinted paint is non refundable, so choose your colours carefully and check that the colour is correct in all cans. Containers must be secured and stored upright during transit. Containers must not be exposed to excessive heat or cold. The use of proprietary additives other than those manufactured by Valspar is not recommended.</p>

Safety Data	
General First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Aust), 0800 764 766 (NZ) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
General Safety Directions	Keep out of reach of children. Avoid contact with skin and eyes. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE.
Further Information	For the latest information refer to the Safety Data Sheet available on our website or contact Valspar Customer Service. Australia Phone: 132 101 Web: www.valspar.com.au New Zealand Phone: 0800 735 551 Web: www.valspar.co.nz

- This information is provided with respect to the listed Valspar products. Valspar Paint (Australia) recommends that:
 - You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product;
 - the product be used only in accordance with the information provided by Valspar;
 - the product be transported and handled in accordance with the SDS and relevant TDS; and
 - you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.
- Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.
- To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Valspar is a registered trademark of The Valspar Corporation, USA
 ZINCALUME® and Colorbond® are registered trademarks of BlueScope Steel Limited.