ULTRA PREMIUM

RESOURCE CODE 512211

NOVEMBER 2013

KITCHEN & BATHROOM CEILING WHITE











Description

Valspar Ultra Premium Paints are designed to make your painting project a more positive experience. Let Valspar help you create a space you can't wait to get home to.

Valspar Kitchen & Bathroom Ceiling Paint is a high-quality, durable interior paint that is ideal for rooms exposed to high humidity and frequent cleaning. Delivering an attractive matt finish, this low-VOC paint is resistant to moisture, mould and mildew. Your chosen colour stays true with Valspar Kitchen & Bathroom.

Why Valspar?

- Mould and Mildew Resistant
- Excellent hiding power
- Low roller spatter

- Hides surface imperfections
- Low VOC
- Low Odour

Colours

White. Tint using Ecotint® to Valspar White based colours or other competitor colours.

Dries to a Matt finish

| Properties & Performance Guide | | |
|----------------------------------|---|--|
| Dry & Recoat Times | Touch Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity. | |
| Coverage per Coat | Up to 14 M ² /L depending on the surface texture, porosity and method of application. | |
| Thinning | Thinning is generally not required. If necessary to aid spray atomisation, thin with up to 5% clean water. | |
| Clean Up | Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first. | |
| VOC (Volatile Organic Compounds) | VOC < 30 g/Litre. | |

ULTRA PREMIUM

RESOURCE CODE 512211

NOVEMBER 2013

PAGE 2 OF 3

KITCHEN & BATHROOM CEILING WHITE

Before Painting

Read safety information below before painting.

- Sound preparation is the key to a perfect finish.
- The surface must be clean, dry and free of dirt, dust, grease and grime.
- Glossy surfaces should be sanded to remove gloss before painting.
- Remove old, loose or flaking paint.
- Repair all damaged areas and sand smooth.
- If mould is present, it must be completely removed. Apply a solution of 1 part household bleach and 3 parts water. Rinse thoroughly with clean water. Allow to dry.
- Seal new fresh plasterboard and bare absorbent surfaces with the appropriate Valspar preparatory coat prior to painting...

Application & After Painting

- Apply when the air and surface temperatures are above 10°C and below 35°C.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Check your colour is correct, as tinted paint is not refundable.
- When more than one container of the same colour is required, intermix containers to ensure
- colour uniformity. If you feel that you may run out of paint, stop at a corner or a natural break.
- Apply 2 full, even coats using a synthetic brush or roller or spray.
 Apply liberally, working from dry areas into the paint's wet edge and finish with gentle, vertical strokes. Avoid excessive rolling or brushing.

AFTER PAINTING

- Remove as much paint as possible from brushes and rollers before cleaning up in soapy water away from drains.
- Wipe up spills immediately with a damp cloth.
- Allow at least 1 week for finish to harden before washing. Only use a mild detergent and water.

| Usage Areas | | |
|--|--|--|
| Usage | Preparatory Coats | |
| Previously painted surfaces | No sealer or undercoat is required on previously painted sound surfaces. Apply one coat of Valspar Acrylic Sealer Undercoat to even porosity on patched surfaces, or to maximise opacity of the topcoat. | |
| New paper-faced plasterboard, unpainted brick, cement render, fibre cement or masonry. | Apply one coat of Valspar Acrylic Sealer Undercoat. | |
| Bare timber and MDF | Apply one coat of Valspar Water Based Primer Sealer Undercoat | |
| New set plaster. | Apply one coat of Valspar Binder Sealer | |

Additional Data

Available in 2, 4 and 10 litre containers.

Tinted paint is non refundable, so choose your colours carefully and check that the colour is correct in all cans.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

The use of proprietary additives other than those manufactured by Valspar is not recommended.



DATA SHEET

ULTRA PREMIUM

RESOURCE CODE 512211

NOVEMBER 2013

KITCHEN & BATHROOM CEILING WHITE

PAGE 3 OF 3

| Safety Data | | |
|--------------------------------|--|--|
| General First Aid Instructions | For advice, contact the Poisons Information Centre on 131 126 (Aust), 0800 764 766 (NZ) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water. | |
| General Safety Directions | Keep out of reach of children. Avoid contact with skin and eyes. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE. | |
| Further Information | For the latest information refer to the Safety Data Sheet available on our website or contact Valspar Customer Service. Australia Phone: 132 101 Web: www.valspar.com.au New Zealand Phone: 0800 735 551 Web: www.valspar.co.nz | |

^{1.} This information is provided with respect to the listed Valspar products. Valspar Paint (Australia) recommends that:

⁽a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Valspar; (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

^{2.} The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.

^{3.} Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.

^{4.} To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.