

ULTRA PREMIUM

RESOURCE CODE 51348-LINE

NOVEMBER 2013

WB TRIM ENAMEL GLOSS

PAGE 1 OF 3



INTERIOR AND EXTERIOR



TINTABLE



WATER WASH UP

Description

Valspar Ultra Premium Trim Enamels are designed to make your painting project a more positive experience. Let Valspar help you create a space you can't wait to get home to.

Valspar Water Based Gloss Trim Enamel protects and accentuates all your interior & exterior trim for beautiful, long-lasting results. This tough and durable enamel paint is easy to clean and gives a tough, durable, non-yellowing coating, providing complete protection.

Why Valspar?

- | | |
|---|---|
| <ul style="list-style-type: none"> • Interior & Exterior • Smooth, tough enamel finish • Non yellowing | <ul style="list-style-type: none"> • Fast Drying • Water Wash Up • Low Odour & Low VOC |
|---|---|

Colours

White, Light, Mid and Strong bases. Tint using Ecotint® to Valspar colours or other competitor colours.

Dries to a Gloss finish

Properties & Performance Guide

Dry & Recoat Times	Touch Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 16 M ² /L depending on the surface texture, porosity and method of application.
Thinning	Thinning is generally not required. If necessary to aid spray atomisation, thin with up to 5% clean water.
Clean Up	Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 60g/Litre.

ULTRA PREMIUM

RESOURCE CODE 51348-LINE

NOVEMBER 2013

WB TRIM ENAMEL GLOSS

PAGE 2 OF 3

Before Painting

Read safety information below before painting.

- Sound preparation is the key to a perfect finish.
- The surface must be clean, dry and free of dirt, chalk, grease and grime.
- Remove old, loose or flaking paint.
- Glossy surfaces should be sanded to remove gloss before painting.
- Repair all damaged areas and sand smooth.
- Finish sanding with 240 grit abrasive paper or finer for the best results.
- If mould, moss, algae or lichen is present, it must be completely removed. Apply a solution of 1 part household bleach and 3 parts water. Rinse thoroughly with clean water. Allow to dry

Application & After Painting

- Apply when the air and surface temperatures are above 10°C and below 35°C.
- In exterior application, do not apply when rain or dew is likely.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Check your colour is correct, as tinted paint is not refundable.
- When more than one container of the same colour is required, intermix containers to ensure colour uniformity. If you feel that you may run out of paint, stop at a natural break.
- Apply 2 full, even coats using a synthetic brush, roller or spray.
- Apply liberally and quickly to form a uniform film, working from dry areas into the paint's wet edge. Finish with gentle strokes along complete sections of the work area. Avoid excessive builds as sagging may result. Do not brush or roll back into partially dried paint.

AFTER PAINTING

- Remove as much paint as possible from brushes and rollers before cleaning up in soapy water away from drains.
- Wipe up spills immediately with a damp cloth.
- Allow at least 1 week for finish to harden before washing. Only use a mild detergent and water.

Usage Areas

Usage	Preparatory Coats
Previously painted surfaces	No undercoat required on sound surfaces. Apply one coat of Valspar Water Based Primer Sealer Undercoat for an even base over patched or damaged surfaces, or to maximise opacity of topcoat.
Interior Bare timber, Hardboard and MDF	Apply one coat of Valspar WB Primer Sealer Undercoat.
Exterior Bare Timber	Apply one coat of Valspar WB Primer Sealer Undercoat. A second coat may be required on tannin rich hardwoods.
Masonry	Apply one coat of Valspar WB Primer Sealer Undercoat
New set plaster	Apply one coat of Valspar Binder Sealer

Additional Data

Available in 1, 2, 4 and 10 litre containers.
Tinted paint is non refundable, so choose your colours carefully and check that the colour is correct in all cans.
Containers must be secured and stored upright during transit.
Containers must not be exposed to excessive heat or cold.
The use of proprietary additives other than those manufactured by Valspar is not recommended.

ULTRA PREMIUM

RESOURCE CODE 51348-LINE

NOVEMBER 2013

WB TRIM ENAMEL GLOSS

PAGE 3 OF 3

Safety Data	
General First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Aust), 0800 764 766 (NZ) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
General Safety Directions	Keep out of reach of children. Avoid contact with skin and eyes. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE.
Further Information	For the latest information refer to the Safety Data Sheet available on our website or contact Valspar Customer Service. Australia Phone: 132 101 Web: www.valspar.com.au New Zealand Phone: 0800 735 551 Web: www.valspar.co.nz

1. This information is provided with respect to the listed Valspar products. Valspar Paint (Australia) recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Valspar; (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.

3. Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.

4. To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Valspar is a registered trademark of The Valspar Corporation, USA

VALSPAR CUSTOMER SERVICE: Ph: 132 101 (AUSTRALIA) – Ph: 0800 735 551 (NEW ZEALAND)